

SCH60 Terminal Head

- **3 x M20 x 1.5 ENTRIES**
- **ALUMINIUM OR STAINLESS STEEL**
- **DISPLAY WINDOW VERSION AVAILABLE**
- **SUITABLE FOR SEM200, 300 AND TT TEMPERATURE TRANSMITTERS**
- **SUITABLE FOR LOOP OR BATTERY POWERED INDICATORS**
- **INTRODUCTION**




The SCH60 terminal head is manufactured from aluminium or stainless steel and is sealed to IP54.

It can house temperature transmitters such as Status Instruments' SEM200, SEM300 series as well as the TTR/TTC 200 range.

In addition, process display products, such as the SEM320 universal temperature transmitter with HART or loop or battery powered displays can also be accommodated.

ORDER CODE: SCH60					
Build order code below.					
SCH60					
Material	Aluminium	A			
	Stainless Steel	S			
Window	Yes			Y	Window is needed for process display products
	No			N	
Example Aluminium Head with window					
SCH60	A	Y			

ACCESSORIES	
31-610-5394-01	SCH60 Pipe mount adaptor
31-630-0016-01	M20 Plug
31-630-0017-01	M20 to 1/2" NPT adaptor
Temperature probe options	Refer to www.status.co.uk or contact sales@status.co.uk



- EARTH
TERMINAL

Approximate weight; 3.0 kg

Ingress protection BS EN 60529: IP54/IP68, in order to achieve IP68 LOCTITE 577 should be used with a M20 O Ring.

The data in this document is subject to change. Status Instruments assumes no responsibility for errors. To maintain full accuracy, annual calibration is required. Contact support@status.co.uk for details

Status Instruments Ltd
Status Business Park
Gannaway Lane, Tewkesbury
Gloucestershire, UK
GL20 8FD

Tel: +44 (0)1684 296818
Fax: +44 (0)1684 293746
Email: sales@status.co.uk
Website: www.status.co.uk

